



Radius (m)	SRC900C, outriggers fully extended, 360, CW 9,5 t														Radius (m)
	12.20	16.55			20.90			25.25			29.60				
2.5	90.00														2.5
3.0	80.00	51.00	28.00												3.0
3.5	75.00	51.00	28.00												3.5
4.0	67.00	51.00	28.00	43.00	28.00	28.00									4.0
4.5	62.00	49.00	28.00	41.00	27.50	27.00									4.5
5.0	56.50	48.00	28.00	39.00	27.00	25.00	28.00	26.00	25.00						5.0
5.5	52.00	47.00	28.00	37.00	25.20	23.50	28.00	24.80	23.50	27.00	23.50	16.00			5.5
6.0	47.00	46.00	28.00	35.00	23.80	22.20	28.00	23.50	22.20	27.00	23.50	16.00			6.0
6.5	43.50	42.00	28.00	33.30	23.00	21.00	28.00	23.00	21.00	26.00	22.50	16.00			6.5
7.0	39.50	39.50	27.70	31.80	22.30	19.80	28.00	21.80	19.80	24.60	21.20	15.20			7.0
8.0	33.00	32.00	27.20	28.00	20.90	17.50	23.00	20.50	17.50	22.00	20.70	14.80			8.0
9.0	24.00	24.50	24.50	23.30	18.00	16.30	21.00	18.00	16.30	20.00	18.10	13.60			9.0
10.0		21.00	21.00	19.70	17.00	15.50	18.00	17.20	14.00	18.50	17.20	11.80			10.0
11.0		17.00	17.10	17.00	16.00	14.00	14.80	16.60	12.60	16.50	16.40	10.60			11.0
12.0		14.20	14.50	14.00	12.80	12.00	11.70	13.90	11.20	14.50	14.00	9.50			12.0
14.0				10.20	10.20	10.50	9.50	10.40	10.20	11.90	10.80	8.60			14.0
16.0				7.60	7.60	7.60	8.00	8.40	8.70	9.30	8.60	7.00			16.0
18.0				5.80	5.80	5.80	6.40	6.60	6.90	7.20	6.90	6.10			18.0
20.0							5.10	5.30	5.50	5.65	5.70	5.40			20.0
22.0										4.40	4.50	4.65			22.0
24.0										3.40	3.70	3.85			24.0
26.0										2.80	2.90	3.20			26.0
28.0															28.0
30.0															30.0
32.0															32.0
34.0															34.0
36.0															36.0
38.0															38.0

